Single TF DBC® SST

Height: 35.7" Width: 12.1" Depth: 22.7" (90.7cm) (30.7cm) (57.7cm)





- Brews 16.3 to 18.9gal (61.7 to 71.5L) of perfect coffee per hour
- Coffee extraction controlled with pre-infusion and pulse brew, digital temperature control, and large sprayhead; coffee strength controlled with variable by-pass.
- Create coffee recipe cards with custom recipes, ad cards with messages that display on the brewer LCD, and dedicated funnels for special coffees with the BrewWISE Recipe Writer using your PC (Windows® compatible).
- Easy pulse interface allows automatic programming of pulse routine
- Preventive maintenance kit: 39641.0000
- SplashGard® funnel and optional funnel locks help improve safety
- Stores individual coffee recipes so operator can easily brew many varieties
- ThermoFresh® servers are vacuum insulated to keep coffee hot for hours.
- Brews 1/2, 1 or 1 1/2gal (1.9, 3.8 or 5.7L) batches
- Energy saver mode reduces tank temperature during idle periods
- Operate any combination of BrewWISE equipment error-free with wireless brewergrinder interface through Smart Funnel with SplashGard®
- Servers not included unless otherwise noted

Agency:

Funnel: Smart Funnel

Specifications

Product #: 34800.6000

Water Access: Plumbed Interface: Wireless

Finish: Stainless

Additional Features

BrewWISE

Electrical & Capacity

| Volts* | Amps | Watts | Cord Attached | Plug Type | 8oz cups/hr 236ml cups/hr | Input H ² O Temp. | Phase | # Wires plus Ground | Hertz |
|--------|------|-------|------------------|-----------|------------------------------|---------------------------------|-------|------------------------|-------|
| - | - | - | - | - | 182 | 60°F (15.5°C) | - | - | - |

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

Plumbing Requirements

| Training requirements | | | | | | | |
|-----------------------|---------|-------------------------|---------------------------|--|--|--|--|
| PSI | kPa | Fitting Supplied | Water Flow Required (GPM) | | | | |
| 20-90 | 138-621 | 3/8" Male Flare Fitting | - | | | | |

CAD Drawings

| 2D | Revit | KLC | | |
|----|-------|-----|--|--|
| • | | | | |

MARNING:



| Unit | | | | Shipping | | | | |
|---------|----------|----------|----------|----------|----------|----------|--------|-----------------------|
| | Height | Width | Depth | Height | Width | Depth | Weight | Volume |
| English | 35.7 in. | 12.1 in. | 22.7 in. | 30.8 in. | 17.5 in. | 26.7 in. | - | 8.311 ft ³ |
| Metric | 90.7 cm | 30.7 cm | 57.7 cm | 78.1 cm | 44.5 cm | 67.8 cm | - | 0.235 m³ |



Related Products & Accessories: Single TF DBC® SST(34800.6000)



Product #: 32643.0000























Serving & Holding Options: Single TF DBC® SST(34800.6000)



TF SERVER, DSG2 1G/3.8L

Product #:42700.0000



TF SERVER, DSG2 1.5G SST

Product #:42750.0000



TF SERVER, DSG2 1.5G BLK

Product #:42750.0001



TF SERVER, DSG2 1.5G CD

Product #:42750.0003



TF SERVER, 1G/3.8L MECH

Product #:44000.0000



TF SERVER, 1.5G/5.7L MECH

Product #:44050.0000



TF SERVER, 1.5G/5.7L MECH BLK

Product #:44050.0001

