



DISHWASHER

CENTER OF ALL YOUR FOOD SERVICE NEEDS

UNDER COUNTER HIGH TEMPERATURE DISHWASHER WITH DIGITAL CONTROL

Item: 46798

Model: CD-GR-0500




High Performance and Quality Under counter Dishwasher

Features:

- Automatic Fill
- · Double skin door
- Automatic drain pump
- Self-cleaning mode
- Built in booster heater
- Built in chemical pumps
- IP 44 washing pump
- Guarantee rinse temperature
- · Self-diagnostic mode
- · 3 washing programs available
- · Easy access for maintenance
- Durable inox construction
- Standard pressure reducer valve (PRV)
- · Standard back cover

Product might not be exactly as shown











DISHWASHER UNDER COUNTER DISHWASHER



PRODUCT SPECIFICATIONS ITEM 46798 MODEL CD-GR-0500 BASKET SIZE 20" x 20"/ 500 x 500 mm POWER SUPPLY 208-240V / 60Hz / 1 Ph POWER 3.6 kW AMP 16 A WASH PUMP MOTOR 0.75 HP

Plug and Wire (not included): Requires a certified electrician to install unit.

WATER CONNECTION	
FLOW PRESSURE	20 psi ± 5
WATER CONSUMPTION / RACK	0.58 gal (2nd program)
WATER CONSUMPTION / HOUR	11.0 gph
WATER INLET CONNECTION	3/4"
DRAINING CONNECTION	1.0"

CAPACITY			
CAPACITY	Booster tank: 6L, Wash tank: 35L		
HEATING ELEMENT	Booster tank: 3 kW, Wash tank: 2.8 kW		
RACK / HOUR (1ST PROGRAM)	28		
RACK / HOUR (2ND PROGRAM)	19		
RACK / HOUR (3RD PROGRAM)	14		
WASH CYCLE 1	103 sec		
WASH CYCLE 2	163 sec		
WASH CYCLE 3	223 sec		
RINSE CYCLE	16 sec		

WORKING TEMPERATURE	
WASHING	72 °C / 161 °F
RINSING	72 °C / 161 °F
MIN-MAX SET POINT TEMPERATURE	30°C - 90°C

Commercial dish washer model: CD-GR-0500

- Rinse with fresh water
- Connection to minimum 55°C water supply
- Guarantee rinse temperature Minimum Maximum set point Temp adjustment: 30°C 90°C









Parts:

- 1. NSF certified indicators for wash temperature, rinse temperature and rinse pressure
- 2. 304 stainless steel body and handle, heavy duty & corrosion resistant
- 3. Upper and lower wash/rinse arms with high temperature cycles
- 4. 1 peg rack, 1 flat rack & 1 cutlery tray included

DIMENSIONS	
DOOR CLEARANCE	14"/ 360 mm
USEFUL DOOR OPENING	12.8" / 325 mm
NET DIMENSIONS (WDH)	22.5" x 24" x 33" / 573 x 617 x 836 mm (38" / 966 mm with door open)
	(oo / oo miii wiiii door open)

GROSS DIMENSIONS 23" x 27" x 38.5" / 590 x 690 x 980 mm GROSS WEIGHT 132 lbs/ 60 kg





NOTE: Normal operation generates steam that may escape from the door. Materials like wood, laminate etc. are unsuitable for areas exposed to dishwasher steam and only stainless steel surfaces is recommended.

OMCAN INC.

Telephone: 1-800-465-0234
Fax: (905) 607-0234
E-mail: sales@ omcan.com
Website: www.omcan.com













