ICB TWIN, 120/240V SST

Height: 26.9" Width: 20.2" Depth: 24.7" (68.3cm) (51.3cm) (62.7cm)





- Sleek modernized design language, with rounded angles on the corners and trunk
- Brews into 2.5 to 3.8L (84 to 128 oz)airpots and 3.8 to 5.7L (1 to 1.5 gallon) baseless Thermofresh servers
- Digital readout displays in English, Spanish, or French ---for easier programming and control--- and can show either 'Standard' or Metric measurements. Digital readout also shows machine status, and targeted advertising messages can be programmed for display.
- Large 5.6 gallon (21.2L) tank provides back-to-back brewing capacity
- BUNN Infusion Series technology allows for multiple recipes from one footprint --with three brew buttons and two batch sizes
- Energy-saver mode reduces tank temperature during idle periods
- The exclusive Peak Extraction® Sprayhead provides improved uniformity of extraction and greater resistance to limescale buildup.
- Electronic funnel lock prevents removal of each brew funnel until drip- through is complete
- USB programming capable
- Brew counter keeps track of how many batches are brewed
- Pre-infusion and pulse brew for maximum flavor extraction. Cold brew lockout & digital temperature control further ensure top-notch brewing.

Additional Features

• Hot water faucet (supplied for custom installation)

Agency:





Specifications

Product #: 53200.6100 Funnel: Black Plastic

Water Access: Plumbed Interface: Wireless Finish: Stainless

Electrical & Capacity

Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H ² O Temp.	Phase	# Wires plus Ground	Hertz
120/240	25	6000	-	-	280	60°F (15.5°C)	1	3	60

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

Plumbing Requirements


PSI kPa		Fitting Supplied	Water Flow Required (GPM)			
20-90	138-621	3/8" Male Flare Fitting	1.00			

CAD Drawings

2D	Revit	KLC		
•	•	•		

MARNING:





Unit				Shipping				
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	26.9 in.	20.2 in.	24.7 in.	30.0 in.	28.4 in.	28.4 in.	78.460 lbs	13.978 ft ³
Metric	68.3 cm	51.3 cm	62.7 cm	76.2 cm	72.1 cm	72.1 cm	35.589 kgs	0.396 m³



Related Products & Accessories: ICB TWIN, 120/240V SST(53200.6100)



FILTERS, GOURMET 500 500/1 50/CL

Product #: 20138.1000

FUNNEL ASSY, SMART COFFEE BLK-CLEARED

Product #: 53463.7107



STAND ASSY KIT, TF SERVER

Product #: 54473.1000



Serving & Holding Options: ICB TWIN, 120/240V SST(53200.6100)



AIRPOT, 2.5L GL PB SINGLE PK

Product #:13041.0001



AIRPOT, 2.5L GL PB 6/ CASE

Product #:13041.0101



AIRPOT, 2.5L SST LA SINGLE PK

Product #:32125.0000



AIRPOT, 2.5L SST LA 6/ CASE

Product #:32125.0100



AIRPOT, 3.0L SST LA SINGLE PK

Product #:32130.0000



AIRPOT, 3.0L SST LA 6/ CASE

Product #:32130.0100



AIRPOT, 3.8L SST LA SINGLE PK

Product #:36725.0000



AIRPOT, 3.8L SST LA 6/ CASE

Product #:36725.0100



STAND ASSY, TF SERVER

Product #:39795.0003



TF SERVER, 1G DSG GEN3 NOBASE

Product #:42700.6250



TF SERVER, 1G MECH GEN3 NOBASE

Product #:44000.6250

STAND ASSY, TF SERVER

Product #:54473.0000

