ICB-DV TALL PE, 120V

Height: 35.0" Width: 10.2" Depth: 22.1" (88.9cm) (25.9cm) (56.1cm)





- 4.3" Color Touchscreen aides in customizing recipes, brewing options and control
- The Infusion Series® Platinum Edition relies on the powerful duo of the Peak Extraction Sprayhead and SmartWAVE® technology to further enhance the uniformity of extraction and resistance to limescale buildup.
- USB programming for uploading and downloading recipes and software updates, all in less than a minute
- Brews into 2.5 to 3.8L (84 to 128 oz) airpots and 3.8 to 5.7L (1 to 1.5 gallon)
 Thermofresh servers
- BUNN Infusion Series technology allows for multiple recipes from one footprint
- Energy-saver mode reduces tank temperature during idle periods
- Electronic funnel lock prevents removal of the brew funnel until drip- through is complete
- Brew counter keeps track of how many batches are brewed
- Pre-infusion and pulse brew for maximum flavor extraction. Cold brew lockout & digital temperature control further ensure top-notch brewing
- Hot water faucet (supplied for custom installation)
- Dual voltage adaptable (Can operate at 120V/15 amp or 120/208-240V/20 amp)
- · Servers not included unless otherwise noted

Agency:





Specifications Additional Features

Product #: 53300.6101
Water Access: Plumbed

Interface: Wireless
Finish: Stainless

BrewWISE

Electrical & Capacity

Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H ² O Temp.	Phase	# Wires plus Ground	Hertz
120	14	1700	-	-	-	60°F (15.5°C)	1	2	60

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

Plumbing Requirements


PSI kPa 20-90 138-621		Fitting Supplied	Water Flow Required (GPM)			
		3/8" Male Flare Fitting	1.00			


CAD Drawings

2D	Revit	KLC
•		

MARNING:







	Unit				Shipping				
	Height	Width	Depth	Height	Width	Depth	Weight	Volume	
English	35.0 in.	10.2 in.	22.1 in.	38.1 in.	14.3 in.	32.3 in.	60.656 lbs	10.139 ft ³	
Metric	88.9 cm	25.9 cm	56.1 cm	96.8 cm	36.2 cm	81.9 cm	27.514 kgs	0.287 m³	



Related Products & Accessories:ICB-DV TALL PE, 120V(53300.6101)



FILTERS, GOURMET 500 500/1 50/CL

Product #: 20138.1000





Serving & Holding Options: ICB-DV TALL PE, 120V(53300.6101)



AIRPOT, 3.8L SST LA SINGLE PK

Product #:36725.0000



AIRPOT, 3.8L SST LA 6/ CASE

Product #:36725.0100



STAND ASSY, TF SERVER

Product #:39795.0003



TF SERVER, 1G DSG GEN3

Product #:42700.6200



TF SERVER, 1.5G DSG GEN3

Product #:42750.6200



TF SERVER, 1G MECH GEN3

Product #:44000.6200



TF SERVER, 1.5G MECH GEN3

Product #:44050.6200

