WQ-TRPL75(10).2L

Height: 22.67" Width: 18.00" Depth: 6.00" (57.6cm) (45.7cm) (15.2cm)



- Protects downstream equipment with exceptional sediment holding capacity and reduces health contaminants such as cyst with 0.2 Microns mechanical filtration
- Certified to NSF Standard 53 for Cyst and Standard 42 for Sediment, Chlorine Taste and Odor reduction
- Sanitary quick connect valve-in-head design simultaneously shuts off and vents water with ¼ turn, allowing for simple cartridge change-outs and maintenance times
- Unique modular filter head manifold design allows for simple installation, customization, and future system expansion
- · Auto-leveling technology ensures perfect installation every time
- High capacity, low pressure drop system configuration
- Select individual filters rated up to 7.5 GPM and 15 GPM
- Selection of filters rated 5 Microns or 0.2 Microns mechanical filtration for dirt and sediment reduction

NOTE: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Specifications

Product #: 56000.0013 Cartridge Type: Quick Change

Application(s): Tea, Ice, Coffee, Backroom Package/Combo System Replacement Cartridge: 56000.0110

Filtration Type: Sediment, Lime Inhibitor, Cyst Reduction, Chlorine Taste & Odor Filter Change Frequency: Annual

Capacity


Micron Rating	Service Flow Rate	Water Filter Capacity Chlorine Reduction	Water Filter Capacity Chloramine Reduction	Water Filter Capacity Softening	
0.2	10.0 gal/min (37.9 L/min)	150000 gal. (567801.6 L)	-	-	


Plumbing Requirements

Inlet Connection	Outlet Connection	Min Operating Pressure	Max Operating Pressure	Min Operating Temperature	Max Operating Temperature
3/4 IN	3/4 IN	20 psi (138 kPa)	125 psi (862 kPa)	40°F(4°C)	100°F(38°C)

MARNING:







Dimensions of Filter System (filter head with filter cartridge)				Installed Dimensions (Installation with wall mounting)			Cartridge Dimensions (filter cartridge only)		
	Height	Width	Depth	Height	Width	Depth	Height	Width	Depth
English	22.67 in.	18.00 in.	6.00 in.	-	-	-	21.32 in.	4.53 in.	4.53 in.
Metric	57.6 cm	45.7 cm	15.2 cm	-	-	-	54.2 cm	11.5 cm	11.5 cm

Weight			Shipping				
	Dry	Wet	Height	Width	Depth	Weight	Volume
English	0.0 lbs	0.0 lbs	8.00 in.	18.00 in.	24.00 in.	21.500 lbs	-
Metric	-	-	20.3 cm	45.7 cm	61.0 cm	9.752 kgs	-


WARRANTY: BUNN High Performance Water Filtration Solutions Systems by BUNN® (excluding water filters and water treatment replacement cartridges) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase, under normal use and service, and when installed in accordance with manufacturer's recommendations outlined in the filtration systems owner's manual. BUNN replaceable elements (water treatment cartridges, filter elements, and feeder elements) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase or the remainder of the original warranty, whichever is longer. See printed warranty for full details. BUNN will provide a copy of the warranty upon request.



Related Products & Accessories: WQ-TRPL75(10).2L(56000.0013)









Model Compatibility: WQ-TRPL75(10).2L(56000.0013) *Serving and Holding selections are currently unavailable. Please contact your sales representative to find out more information.*

