

AJX-66

Rack Conveyor Dishwasher

Standard Features

- Automatic tank fill
- Electromechanical controls
- Adjust-A-Peak™ adjustable conveyor speed allows for extension of wash time and rinse contact for heavy soil conditions
- 25" (635 mm) vertical chamber clearance accommodates larger ware, such as sheet pans and mixing bowls
- 22" (559 mm) pre-wash section has two upper and one lower pre-wash arms
- Exclusive EnergyGuard™ controls
- Stainless steel scrap baskets
- Splash shields
- 18" (457 mm) wash section with 18" (457 mm) separation between wash and rinse sections
- Self-draining stainless steel wash pump
- Vent fan control shuts vent fan off when machine is idle
- Stainless steel front dress panel
- Adjustable bullet feet
- Externally operated drain lever
- 18kW wash tank heater
- Durable stainless steel construction

Options & Accessories

- | | |
|--------------------------------|--------------------------------------|
| ➤ 460V Electrical | ➤ Strikeplate Table Limit Switch |
| ➤ Booster Heater | ➤ Flanged Feet |
| 40 °F (22.2 °C) Rise - 17kW | ➤ Security Package |
| 70 °F (38.9 °C) Rise - 30kW | ➤ Scaltrol |
| ➤ Blower Dryer | ➤ Replacement Cartridge for Scaltrol |
| ➤ Side Loader | ➤ 36-Compartment Rack |
| 23" (584 mm) Unhooded | 4-1/8" tall (105 mm) |
| 23" (584 mm) Hooded | 5-5/8" tall (143 mm) |
| 30" (762 mm) Unhooded | 7" tall (178 mm) |
| 30" (762 mm) Hooded | ➤ Combination Rack |
| ➤ Drain Water Tempering Kit* | ➤ Peg Rack |
| ➤ Water Hammer Arrestor | ➤ Sheet Pan Rack |
| ➤ Pressure Regulator | |
| ➤ Vent Cowl Collars (set of 2) | |



Specification Statement

Specified unit will be a Jackson AJX-66 rack conveyor dishwasher, rated by NSF to NSF/ANSI Standard 3. High temperature model to be rated for 225 racks per hour, and will consume 0.68 gallons of water per rack. Chemical sanitizing model to be rated for 209 racks per hour, and will consume 0.78 gallons of water per rack. Features include a 22" pre-wash, EnergyGuard™ controls, 25" vertical chamber clearance, automatic tank fill, self-draining 2.0 HP stainless steel wash pump motor, and vent fan control. Constructed of durable stainless steel with available flanged feet option.

1-year parts and labor warranty.

Mandatory Specs

- Voltage_____
- Sanitizing Method
 - ☐ High Temperature
 - ☐ Chemical Sanitizing
- Direction of Operation
 - ☐ Left to Right
 - ☐ Right to Left





Right to Left

LEGEND

- A - Water Inlet
(3/4" NPT, 110–140 °F MIN)
- B - Electrical Connection
- C - Drain Connection (1 1/2" NPT)
- D - Vent Collar - Optional
- E - Vent Cowl - Standard
- F - Pre-wash Water Inlet
(3/4" NPT, 110–140 °F)
- G - Cold Water Thermostat - Optional
(3/4" NPT)

All dimensions from the floor can be increased 1" using the machine's adjustable feet.

Items in red are not supplied with the machine.



Left to Right

LEGEND

- A - Water Inlet
(3/4" NPT, 110–140 °F MIN)
- B - Electrical Connection
- C - Drain Connection (1 1/2" NPT)
- D - Vent Collar - Optional
- E - Vent Cowl - Standard
- F - Pre-wash Water Inlet
(3/4" NPT, 110–140 °F)
- G - Cold Water Thermostat - Optional
(3/4" NPT)

All dimensions from the floor can be increased 1" using the machine's adjustable feet.

Items in red are not supplied with the machine.








Table Fabrication



Operating Capacity

Racks per Hour	
High Temperature	225
Chemical Sanitizing	209
Dishes per Hour	
High Temperature	5,625
Chemical Sanitizing	5,225
Glasses per Hour	
High Temperature	8,100
Chemical Sanitizing	7,524

Operating Speed

Conveyor Speed (feet per minute at highest speed)	
High Temperature	6.20 FPM (1.9 MPM)
Chemical Sanitizing	5.75 FPM (1.8 MPM)

Operating Temperature

Pre-wash Temperature (minimum)	110-140 °F (43-60 °C)
Wash Temperature (minimum)	
High Temperature	160 °F (71 °C)
Chemical Sanitizing	140 °F (60 °C)
Rinse Temperature (minimum)	
High Temperature	180 °F (82 °C)
Chemical Sanitizing	140 °F (60 °C)

Water Consumption

Gallons per Rack	
High Temperature	0.68 (2.6 L)
Chemical Sanitizing	0.78 (3.0 L)
Gallons per Hour	
High Temperature	153.00 (579.2 L)
Chemical Sanitizing	163.02 (617.1 L)
Flow Rate (GPM)	
High Temperature	2.57 (9.8 LPM)
Chemical Sanitizing	2.74 (10.4 LPM)
Pre-wash Tank Capacity (gallons)	17.25 (65.3 L)
Wash Tank Capacity (gallons)	21.00 (79.5 L)
Pre-wash Pump Capacity	120 GPM (454 LPM)
Wash Pump Capacity	270 GPM (1,022 LPM)

Water Requirements

Incoming Water Temperature	
High Temperature	180 °F (82 °C)
Chemical Sanitizing	140 °F (60 °C)
Flow Pressure (PSI)	15
Incoming Water Connection (NPT)	3/4"
Drain Connection (NPT)	1 1/2"

Electrical Specifications

Pre-wash Pump Motor (HP)	1.0
Wash Pump Motor (HP)	2.0
Drive Motor (HP)	1/4
Wash Tank Heater (kW)	18.0

Venting Requirements (CFM)

Input End	200
Output End	400
Total	600

Dimensions

Width	84" (2134 mm)
Width between tables	66" (1676 mm)
Depth	25" (635 mm)
Height	75 1/2" (1915 mm)
Height with Door Open	84" (2134 mm)
Inside Clearance Height	25" (635 mm)
Wall Clearance	4" (102 mm)
Drain Height	9 3/8" (238 mm)
Weight	800 lbs (363 kg)

Shipping Details

Shipping Weight	1000 lbs (454 kg)
Shipping Width	96" (2438 mm)
Shipping Depth	40" (1016 mm)
Shipping Height	78" (1981 mm)
Shipping Cube	173.33 cu ft
Shipping Class	200

Electrical Schedule

Power Supply	Total Load	Minimum Circuit Ampacity	Maximum Overcurrent Protection
AJX-66CE			
208/60/3	61.0 A	62.5 A	65.0 A
230/60/3	52.1 A	53.6 A	55.0 A
460/60/3	26.1 A	26.9 A	30.0 A
AJX-66CEL			
208/60/3	60.3 A	61.7 A	65.0 A
230/30/3	51.5 A	52.9 A	55.0 A
460/60/3	25.7 A	26.5 A	30.0 A

Booster Heater Options

Power Supply	kW	Amps
40 °F (22.2 °C) Minimum Rise Booster		
208/60/3	17.2 kW	47.8 A
230/60/3	18 kW	45.2 A
460/60/3	18 kW	22.6 A
70 °F (38.9 °C) Minimum Rise Booster		
208/60/3	30 kW	83.4 A
230/60/3	18 kW	75.4 A
460/60/3	18 kW	37.7 A

Advisory: Jackson WWS, Inc. DOES NOT endorse "Tankless On-Demand" water heaters for use with our dishmachines. Jackson WWS, Inc. DOES endorse, and highly recommends, standard "tank" style water heaters, sized to properly handle the water heating requirements of the facility.

CONTACT JACKSON

07610-003-78-21 [07/01/26]

Address

6209 N U.S. Highway 25E
Gray, Kentucky 40734

Website

www.jacksonwws.com

Telephone & Fax

T 888.800.5672
F 606.523.1799

Email

customer.service@jacksonwws.com



@JACKSONWWS



JACKSON WAREWASHING SYSTEMS



JACKSON WWS



@JACKSONWAREWASHING