



IM-o46o Ice Cube Machine

Models

- IM-o46o-AC IM-o46o-AH IM-o46o-WC IM-o46o-WH




ICETRO IM-o46o ice machine on a IB-033 bin

*Ice Machine and Bin sold separately

- Up to 444 lbs production capacity (70F/50F, 24 Hours)
- 304 stainless-steel exterior (durable & rust-resistant)
- Simple diagnostic panel to assist service & maintenance
- Cleaning switch for auto cleaning cycle
- Magnetic frame cleanable condenser air filters
- Adjustable flush time to reduce scale & cleaning cost
- ABS antimicrobial interior to reduce slime & cleaning cost
- Water distributor tube & water sump removed w/o tools
- Heavy duty water curtain, pins & hangers for easy removal
- Hinged front doors for easy access
- No screws on side or back panels for easy access
- Sides & top vents for optimal ventilation
- Improved evaporator section to reduce airborne bacteria
- Power cord with NEMA 5-15 plug
- R-404A refrigerant

Ice Shape



Half Cube
 $\frac{3}{8}'' \times 1\frac{1}{8}'' \times \frac{7}{8}''$
(.95 x 2.86 x 2.22 cm)



Cube
 $\frac{7}{8}'' \times \frac{7}{8}'' \times \frac{7}{8}''$
(2.22 x 2.22 x 2.22 cm)

Factory Warranty

Parts & Labor **3** YR Parts **5** YR Parts **5** YR
Ice Maker Evaporator Compressor



Extend parts & labor warranty 1 year by installing an IcePro filter/cartridge and by registering it at: icetrowaterproducts.com/registration/

* Applies only to new ice machines, at the time of original installation & start-up.

** Requires replacement of the filter cartridge every 6 months or earlier

Specifications

BTU Per Hour:

6,184

Refrigerant:

R404A

- Ambient Temperature Range: 50 to 100 F (10 to 37 C)
- Water Temperature Range: 50 to 90 F (10 to 32 C)
- Potable Water Pressure: Min. 20 psi (137.9 kPa) Max. 80 psi (551.1 kPa)
- Condenser Water Pressure: Min. 20 psi (1.38 bar) Max. 150 psi (10.34 bar)

Ice Machine Electric

115/60/1

Minimum circuit ampacity:

Air-cooled: 15 *1ph*

Water-cooled: 15 *1ph*

Maximum fuse size:

Air-cooled: 25 *1ph*

Water-cooled: 25 *1ph*

Accessories

Bin-Stat Kit IBO-150KIT

Recommended when ice machine is installed on soda dispenser.



Water Filtration IcePro 500 (replaces Icepro 400)


Reduces sediment and chlorine contaminants with the use of Citrine.






IM-o46o Ice Cube Machine

IM-0460 Air Cooled



IM-0460 Water Cooled



FRONT VIEW

SIDE VIEW

BACK VIEW

Specifications

Dimensions	Width	Depth	Height	Weight
IM-0460 Machine	30"	24.8"	22.6"	162.3 lbs (Net) 195 lbs (Shipping)

Model	Ice Shape	Ice Production 24 Hours		Power Usage kWh/100 lbs. @90°Air/70°F	Potable Water Usage/100 lbs. 45.4 kgs. of Ice*
		70°Air/ 50°F Water	90°Air/ 70°F Water		
AIR COOLED	cube	1 ph	1 ph	1 Ph	15 Gal.
		444 lbs	376 lbs		
	half-cube	444 lbs	376 lbs	5-43	15 Gal.
		201 kgs	171 kgs		
WATER COOLED	cube	463 lbs	407 lbs	4-56	15 Gal.
		210 kgs	185 kgs		
	half-cube	463 lbs	407 lbs	4-56	15 Gal.
		210 kgs	185 kgs		



*Water-cooled condenser uses 82.1 gal/100 lbs. of ice

