



- Pass-through dishwasher;
- Stainless steel construction 18/10 AISI304;
- Wash cycle time: 1'-2'-3' minutes;
- Linear/Corner version;
- Soft touch electronic control panel;
- Temperature's electronic display;
- Cycle start at hood closing;
- Stainless steel lower and upper rotating wash arms;
- Stainless steel lower and upper rotating rinse arms;
- Double skin self-washing slanted tank with rounded edges;
- Integral tank filter;
- Rinse aid dispenser;
- Detergent pump,
- Automatic tank loading;
- Hood opening safety device;
- Thermocontrol: device which guarantees the selected temperature for every rinsing cycle even in case of non-stop work;
- Security thermostat;
- Certifications: UL, UL Sanitation;




SIZE:
26.38x30.12xH57.09 inch
Cycle period: 1'-2'-3' minutes
Capacity per hour:
Baskets/H 60/30/20
Dishes/H : 1080/540/360
Dishes per basket 12÷18




L25-ek

Accessories:
2 baskets for dishes;
1 generic basket;
2 cutlery containers;



TABLES NOT INCLUDED



Specifications	L25-ek	
VOLTAGE	208-240V 3ph 60Hz	V
WASHING PUMP	650	W
WASH TANK ELEMENTS	2000	W
RINSE TANK ELEMENTS	6000	W
TOTAL RATING	6650	W
MAX CURRENT INTENSITY	34	A
PLATES CLEARANCE	16,34	inch
WORK HEIGHT	34,25	inch
TANK CAPACITY	34	Lt.
BOILER CAPACITY	8	Lt.
PUMP DELIVERY	550	Lt./min
WATER CONNECTION	131	°F
WATER CONSUMPTION PER CYCLE	2,60	Lt.
WATER CONSUMPTION PER HOUR	58÷117	Lt.
WATER PRESSURE	20±5	psi
WATER HARDNESS	5 + 10	TH(°F)
RINSING WATER TEMPERATURE	179 + 194	°F
WATER INLET	3/4"	"G
WATER OUTLET	1"1/4	"G
NET WEIGHT	148	Kg
GROSS WEIGHT	156	Kg
PACKING SIZE	29,92xL33,86xH56,30	inch
NOISE LEVEL	<60	dB(A)

The manufacturer reserves the right to make modifications of materials and models without warning.