

Model

e5-1530



Standard Features

- Advanced Cooking Technology* combines two heat technologies of convection and microwave for fast, even heating of food product
- Up to five (5) times faster than conventional cooking methods
- “Ventless” Cooking” capability through standard built-in catalytic converter with full protein capability
- Ability to use a standard, ½ size metal baking pan while in convection mode
- Automatic voltage detection (U.S. only)
- Cool to touch door exterior
- MenuConnect™ - Ethernet connection for remote uploads to menus and diagnostics

*Local codes prevail. These are the “authority having jurisdiction” as stated by the National Fire Protection Association, Inc., in NFPA96-1994.


Specifications

Construction

- 430 stainless steel casework and 304 stainless steel interior cavity
- Easy side panel access to internal components
- Easily accessible, front facing air filter

EasyToUCH™ Control Panel

- Icon driven, color touch screen control panel with the capability of storing up to 1,024 multi-stage recipe programs
- Each program offers up to six (6) stages with programmable cooking times, microwave power settings and user instructions for each stage
- Self diagnostics capability to monitor components
- Easy menu updates or data transfer via USB memory stick
- Multi-language capability



(Top view)

The convection fan (1) draws air from the oven cavity, circulating it over the heating elements (2) to obtain the set temperature and through the catalytic converter (3) to clean the air before returning it to the oven cavity.



Model e5-1530

Overall Size			Specifications	
Height	25.3"	642 mm	Preheat Time	15 minutes
Width	28"	712 mm	Control System	easyToUCH™, iconic symbol touch screen control panel
Depth (overall with handle)	27.8"	705 mm	Cooking Stages	6
Depth (door open 90 degrees)	39"	990 mm	Total Cooking Programs	1,024
Weight	207 lbs	94 kg	Maximum Cooking Time	60:00 (10:00 x6 Stages)
Shipping Weight	235 lbs	106.5 kg	Defrost	No
Shipping Box Size	37.4 x 30.3 x 33.85"	950 x 770 x 860 mm	Microwave Distribution System	Rotating Active Antenna
Oven Cavity Dimensions			Magnetron(s)	2
Height	10.2"	259 mm	Display	Touchscreen
Width	19.5"	495 mm	Interior Light	No
Depth	14.1"	358 mm	Automatic Voltage Sensor	Yes
Wall Clearance			USB & MenuConnect Software	Yes
Top	2"	50.8 mm	Temperature Range	Off, 212°F - 482°F
Sides	2"	50.8 mm	Temperature Increments	1°F (from 212°F upwards)
Electrical Specifications			Air Filter	Yes - removable
Phase	1 ph		Convection Fan Speed	High
Voltage	208 / 240		Convection Fan Speed Increments	N/A
Frequency	60Hz		Microwave Power	0%(off), 5%-100%
Amperage Requirement	30 amp	 NEMA 6-30P	Microwave Power Increments	1% (from 5% upwards)
Plug	NEMA 6-30P		Rack	Yes - 1
Cord Length	6 ft		Rack Positions	2
Power Consumption	6200W		Turntable	No
Power Output (Microwave)	1400W		Stackable	No
Power Output (Convection)	3.2kW		Warranty	1 year parts and labor
Accessories in Box				
			Chemco Dirt Buster III Cleaner	1 unit
			Chemco Oven Shield	1 unit
			Spray Triggers	2 units
			Operator Manual / Cleaning Instructions	1 unit
			Cool down tray	1 unit
			USB Key	1 unit

For further information on Merrychef products and service or advice on which machine suits you best please contact your sales representative or visit our website at www.merrychef.com.

Specifications subject to change without notice.

Merrychef U.S.A
 1111 N. Hadley Rd.
 Ft. Wayne, IN 46804

Tel: 877-404-6872
 Fax: 800.285-9511
 E-Mail: info@merrychefusa.com

www.merrychef.com
 MCF_6024 1/18/16

