

Blixer® 7



7.5 L

A SALES FEATURES

Blixer® 7 is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

B TECHNICAL FEATURES

Blixer® 7. 3-phase. Power: 3 HP. Speeds: 1800 and 3600 rpm. 7.5 L stainless-steel bowl with handle, plus bowl-base, fine-serrated, twin-blade assembly. Watertight lid with Blixer® arm. 3 - 25 portions (7 oz).

Select your options at the back page, **F** part.

C TECHNICAL DATA

Output power	3 HP
Electrical data	208-240V/60/3 - 4.7-8.8 A
Speeds	1800 and 3600 rpm
Dimensions (WxDxH)	10 7/16" x 13 25/64" x 22 7/16"
Rate of recyclability	95%
Net weight	47.5 Lbs
Nema #	L15-20P
Reference	BLIXER 7 - 208-240V/60/3

D

Number of 7 oz portions per service



Amount processed per operation

1 to 8 lbs

E PRODUCT FEATURES / BENEFITS**MOTOR UNIT**

- Industrial direct-drive (no belt) induction motor designed for intensive use
- Power 3 HP
- Stainless-steel motor shaft
- All-metal motor base
- Magnetic safety system, thermal failsafe
- **Speeds: 1800 and 3600 rpm**
- Pulse function for greater cutting precision

BLIXER® FUNCTION

- **7.5 L stainless-steel bowl** with handle for better grip.
- **Bowl-base blade assembly** with two high-strength, stainless-steel, fine-serrated blades for homogeneous processing – even for small amounts.
- **Central lid opening** for adding liquid or solid ingredients during processing.
- High heat and shock-resistant **see-through lid** to monitor processing from start to finish.
- Watertight bowl-lid assembly with Blixer® arm
- All parts are dishwasher-safe and can easily be removed for cleaning.

STANDARD ATTACHMENTS

- 7.5 L bowl with lid.
- Blixer® arm and lid wiper
- Blade assembly with two fine-serrated, stainless-steel blades and a detachable cap.

STANDARDS

ETL electrical and sanitation Listed/ cETL (Canada)



Blixer® 7

F OPTIONAL ATTACHMENTS

- Additional all stainless steel fine-serrated twin-blade assembly Ref 27313
- Additional composite fine-serrated twin-blade assembly Ref 27316
- All stainless steel coarse-serrated twin blade assembly for grinding and kneading - Ref 27314
- Composite coarse-serrated twin blade assembly for grinding and kneading- Ref 27317

G ELECTRICAL DATA

208-240V/60/3 – delivered with cord and plug.

